

# Grease Jockey® Recommended Lubricants and Lubricant Selection

Lubricants satisfactory for use in Grease Jockey systems must not be susceptible to separation when under pressure. This is important because the system is operated only during infrequent intervals, and the quantity of the lubricant discharged per cycle is small.

Another consideration is the “pumpability” of the lubricant through long lines. In many cases, the lines are exposed to ambient temperatures, which may be low in winter months, for all or part of their length. In such installations, it is apparent that the lubricant must be “pumpable” to be suitable for use.

The Grease Jockey system can handle lubricants with viscosities of 55 SUS @100°F (ISO 9@ 40°C), up to 250 SUS @ 210°F (ISO 54@100°C).

1. NLGI Grade – NLGI Grade “0” can be used for temperatures of 50°F or above year round. If ambient temperature is ever below 50°F, NLGI Grade “00” should be used.
2. Type of Soap Additives – Lithium, calcium, or aluminum complex soaps are desirable. However, compatibility should be checked with current grease type.
3. Type of Additives – Greases with extreme pressure (EP) additives are recommended for longer part life.

**CAUTION:** The use of Moly Disulfide grease is not recommended as the Moly particles may plug the meters.

**NOTE:** For additional lubricant recommendations, contact your Grease Jockey distributor or the factory.

## IDENTIFICATION AND SELECTION OF METERS



Meter Identification and Usage				
Meter Size	Number of washers	Hex Flat	Output (in³)	Recommendations for specific lubrication points
0	0	No	0.002	Brake Shafts, transmissions, cross shafts, “S” cams
1	1	No	0.005	Slack adjusters, 5th wheel pivot, and miscellaneous points
2	2	No	0.009	Drag link, tie rod ends, power steering linkage
3	3	No	0.012	King pins, spring pins, spring shackles
4	4	No	0.015	Miscellaneous other points
8	4	Yes	0.025	5th wheel plate

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

## Contact us today!

To receive product information or talk with a Graco representative, call 800-533-9655 or visit us online at [www.graco.com](http://www.graco.com).